SV-2YT

VERTICAL MACHINING CENTER

August 1, 2026

Prices and specifications are subject to change without notice.
Pictures and graphics are representative and may not be from the actual machine.

MACHINE SPECIFICATIONS

	SV-2YT
CAPACITY	
X axis travel	31.5”
Y axis travel	19.7”
Z axis travel	19.7”
Table size	19.6” x 39.2”
Table loading capacity	1,320 lbs.
SPINDLE	
Distance from table top to spindle nose	3.94” – 23.6”
Distance from column to spindle center	22.04”
Spindle taper	CAT40 (BIG PLUS)
Spindle speed	12,000 rpm
AC Spindle motor	20/ 25 hp
Spindle Torque (30 min)	87 ft.-lbs.
AUTO TOOL CHANGER	
Magazine capacity	30
Tool shank	CAT40 (BIG PLUS)
FEED RATE	
Rapid traverse (X / Y / Z)	1,890 ipm
Cutting feedrate ipm	394 ipm
Slide Ways	Linear Way
COOLANT TANKS	
Front Tank Capacity	36.98 gallons
Side Tank Capacity	68.68 gallons
GENERAL	
Floor space (L x W) (including conveyor)	134.65” x 82.68”
CNC Model	Fanuc 0i-MF Plus (15” screen)

Prices and specifications are subject to change without notice.
Pictures and graphics are representative and may not be from the actual machine.

INVESTMENT

BASE PRICE:	**SV-2YT (CAT40, 12K)**	**$84,900.00**

SMART PACKAGE:

- 30 Tools Double Arm ATC
- Full Enclosed Splash Guard
- Coolant Bed Flush
- Rigid Tapping
- Big Plus Spindle
- Manual Guide i
- Lift Up Conveyor

SMART VALUE PACKAGE:

- Renishaw Receiver and GUI software
- 280 PSI CTS
- Air Thru Spindle
- 4 Axis Preparation
- Coolant/Air Gun
- Spindle Oil Cooler
- High Speed Machining, 200 Look Ahead

SMART VALUE PACKAGE PRICE:	**$5,000.00**
TOTAL PACKAGE PRICE:	**$**
STOCK PRICE:	**$**

FOB: Port of Entry
Terms: 20% Down, Balance Net 15 Days from Shipment

OPTIONAL EQUIPMENT

▪ Renishaw Probe and Tool Setter (When Purchased with Machine)	$1,995.00
▪ CNC-200R Rotary Table (beta)	$14,900.00

Prices and specifications are subject to change without notice.
Pictures and graphics are representative and may not be from the actual machine.

Warranty

The machine is warranted against defects in parts, material and workmanship for a period of twelve (12) months after the date of installation. The control, servomotors and main spindle motor are warranted against defects in parts, material and workmanship for a period of twenty-four (24) months after the date of installation.